

Glossary of Terms in Powder & Bulk Technology View PDF

4. Powder Processing

Written by Lyn Bates - edited by mhd on 18. Sep. 2022

The placing together of different materials in a prescribed ratio at a scale of scrutiny that is significant to the application by way of low energy mechanisms, such as by intermingling gravity flow streams or layering onto a moving belt. (See mixing and homogenising).

'boiling' fluid bed

A fluid bed where the quantity of the fluidising media agitates the mass by passing through the bed in large bubbles.

calcining

blending

A process of modifying the properties of a powder by subjecting it

to a high temperature.

The converging region between the rollers of a roll press where the surface friction on the product causes the material to move

towards the nip point without slipping on the roller surfaces.

cementation

capture zone

The binding together of particles by precipitation at their points

of contact.

cold pressing The compaction of a powder carried out at room temperature.

comminution The reduction of particles size by intensive fracture.

compact A form prepared by compressing powder in a mould or die.

compact,

(See green compact).

green

compact, sintered	A green compact after sintering.
cut	The division point for separating a flow stream in which particles are preferentially directed to each side of the 'cut' according to some physical attribute.
dilated bed	A bed of powder that is expanded to a dilate condition by a gas pressure in the voids in excess of ambient. (See settling bed, expanded bed).
dry inertial collectors	A type of dust collector that disengages particles from a gas by virtue of exploiting their physical dynamics.
electrostatic precipitators	A dust collecting system that imparts an electric charge to particles in a dust laden stream and subsequently collects them on plates maintained at a high voltage.
expanded bed	A bed of particulate solids held in a state of dilatation by the upwards passage of a second phase media such that the particle-to-particle contact pressure is reduced from that of a settled bed. (See dilated bed).
fabric filters	A dust collecting system that uses porous fabric as a barrier to collect dust particles.
fluid bed	A suspension of particles suspended in an upward flow of fluid (or downward flow if the particles are less dense than the fluid). The bed may be quiescent or boiling, according to the quantity of the fluidising fluid.
fluidising	The process of injecting a gas underneath a bed of particulate solids, to dilate the material in a rising gas stream such that it behaves like a liquid. See fluid bed.
granulation	The process of combining particles into larger agglomerates (granules).
green compact	A formed compact intended for sintering, or which hardens with time or other treatment.
Haultain infrasizer	A vertical air elutriator similar to the roller elutriator.
homogenising	The rendering of components that were initially separate or varied in nature throughout the volume of a mass, to a compound of uniform composition at a scale of scrutiny that is

significant to the application. (See blending and mixing).

The compaction of a powder under heat and pressure, to result in hot pressing sintering of the mass to a strongly bound mass. The minimum gas velocity required to fluidise a bed of powder. minimum fluidising The value depends mainly upon the particle size and effective velocity particle density. The conditions which occurs when particles wedge in the pegging apertures of a sieving medium. An agglomerate of particles produced by specialised techniques, pellet such as pressing. A heat treatment carried out at a temperature below a final pre-sintering sintering temperature to strengthen a powder compact. pressing The compaction of a powder under pressure in a mould or die. (See cold pressing). pressing, cold pressing, hot (See hot pressing). pressing, warm (See warm pressing). A bed of particulates held in a steady, tranquil state of suspended quiescent bed dilatation by the passage of a second phase media. A vertical air elutriator used for fractionating powder in the size roller elutriator range 5 to 300 microns. A compacting device that consolidates powder between two contra- rotating rollers under a nip pressure acting on the small roll press gap between the rollers. The rollers may have flat surfaces, to produce flakes, or have mould indentations that form pellets or nodules. The separation of a small amount of oversize lumps or particles scalping from a bulk material by size classification. A stable bed of particulates where particle to particle contact settled bed pressure is fully developed and not relieved by internal void pressure or the counter-flow of a fluid. A transient condition, where a bed of dilated particles has an increasing density condition and a decreasing void pressure as the media in the interstitial volume at a higher pressure than settling bed ambient percolates from the bed, ultimately to allow particle-toparticle contact pressures to develop to those of a fully-settled

bed where the void pressure is ambient.

The reduction in size of a compact on drying or sintering,
shrinkage expressed as a percentage of the final volume or stated linear dimension.

The bonding of contiguous particles in a mass of powder or a compact by partial fusion at temperatures below the melting point of the particles.

A device for fractionating fine particles by moving a fluid stream in which the particles are suspended through a cylindrical vessel from a tangential inlet to a more centrally located outlet. The

spiral flow extend to which centripetal forces on the particles overcome fluid drag is related to the physical characteristics of the individual particles and determines the ability of the particles to exit at specific radially located outlets of the equipment. The division between outlet positions being terms the 'cut'.

tablet A small compact.

The path taken by a particle with an initial component of trajectory horizontal motion under the influence of gravity and/or prevailing

air flow.

warm pressing The compaction of a powder under pressure above room temperature and below sintering temperature.

wet scrubbers A dust collecting system that employs a spray system to capture particles.

- < 3. Powder Properties
- Up
- 5. Particle Properties >

