



Produktneuheiten

BEUMER Group: Determining the venting capacity of bags with a mobile unit

Bearbeitet von am 27. Okt. 2017

Beckum, Deutschland –

Bags filled with bulk material are then stacked flat on pallets after being closed. These stacks are only stable if the air has been removed from the bags lying on top of each other. Therefore, the remaining air needs to escape from the filled bags before they are closed. The quicker this happens, the higher the filling capacity. The new **BEUMER bag tester** provides users with important information on the filling behaviour of each bag. This is relevant for the manufacture of bags and filling technology, as well as for transport and logistics.



Picture 1: The BEUMER bag tester enables users to exactly determine the venting capacity of any type of valve bag.

A pressure-compensated flow control valve on the device constantly increases the volume flow rate until a steady pressure of 50 mbar is reached. With this pressure, the user can read the current volume flow rate, which indicates the air permeability, from the flow-rate meter. A filling spout with inflatable sleeve seals the bag valve during the air flow measurements. The scope of supply includes an additional inflatable sleeve for valve widths of up to 200 millimetres.

worldwide, the **BEUMER Group** has annual sales of about EUR 750 million.

BEUMER Group and its subsidiaries and sales agencies provide their customers with high-quality system solutions and an extensive customer support network around the globe and across a wide range of industries, including bulk materials and piece goods, food/non-food, construction, mail order, mail and airport baggage handling.