



Product News

Flexco skirting systems effectively stop material spillage at the transfer point

Edited by on 27. Oct. 2017

High throughput, low dust levels Flexco offers various skirting systems to avoid loss of material in belt conveyor transfer areas in coal mines, steel mills and wood processing facilities. Fasteners combined with skirting systems effectively isolate the material on the belt without damaging the belt cover, enabling operators to easily reduce dust levels while increasing material throughput. Flexco supplies easy-to-install skirt clamps for a wide range of load levels.

Flex-Lok skirt clamps are a new addition to the [Flexco](#) range: customised for various conveyor systems, they are even suitable for large and heavy-duty conveyance tasks. On the other hand, **Flex-Lok Mini Clamps** are ideal when space is limited – the rubber sealing strip is only 8 to 16 millimetres thick, while the thickness of the standard version is between 8 and 25 millimetres. Flex-Lok skirt clamps can be easily installed by one person, because the clamp plates position the retaining rod of the rubber sealing strip. The skirt clamps can be mounted diagonally or vertically on the conveyor structure.



Photo 1: Flexco supplies Flex-Lok skirt clamps for a wide range of load levels. They can be easily installed by one person.

The ***Flex-Seal skirting system*** is a dynamic containment unit which completely seals the loading zone parallel to the belt. The system reduces dust levels by

closing gaps through which material can spill. Problems such as belt damage and belt wander no longer occur. The thickness of the Flex-Seal rubber skirt varies between 8 and 19 millimetres with this solution. Flexco also offers a cost-effective solution that is especially suitable for confined spaces – the RMC1 skirting system. All three of these [Flexco](#) solutions are designed for easy installation – the clamp bolts are designed to allow the clamp wedge to rotate through 360°, locking it in place, and an additional anti-vibration clamp pin ensures that the clamp bolt remains in place even under extreme conditions. Service technicians can safely perform installation and maintenance work on the skirting system from the sides of the conveyor system. The individual system components are corrosion-resistant and highly resilient to ensure a long service life.



Photo 2: The RMC1 skirting system by Flexco is a cost-effective and space-saving solution.

(Photo credits: Flexco Europe GmbH)

In the case of all three systems, the skirt rubber exerts no tension at all on the belt, causing no premature wear or scratches on the belt cover. The **Flexco** range includes the rubber LRS15-R and LRS15 PU skirts, which are simply to install and quick to service. They offer highly effective solutions in combination with the fasteners. No bolt, nuts or additional special tools are required for assembly.

About the FLEXCO Flexible Steel Lacing Company (FLEXCO), headquartered in Downers Grove, Illinois in the USA, is the leading international specialist for

*mechanical conveyor belt fastener systems, belt cleaners, belt positioners, impact beds and pulley lagging for light- and heavy-duty applications. With the company's innovative solutions, endusers can substantially reduce downtime and increase productivity. **FLEXCO Europe GmbH** is the German subsidiary of **FLEXCO**, and is headquartered in Rosenfeld, where the company currently has about 60 employees.*