



REV	DATE	BY	CHKD

CONSTRUCTION

Q/M/10/04/901

DETAILS OF HOPPER

- DO NOT SCALE WORK TO DIMENSIONS ONLY.
- ALL CONCRETE SURFACES SHALL BE WETTED WITH 6 MM THICK FLEET WELD.
- ALL CORNER JOINTS SHALL BE 8 MM THICK (0.25).

THIS DRG. IS TO BE READ IN CONJUNCTION WITH OUR FOLLOWING STD. DRG. & SPECIFICATIONS:

- AI-100-SB-01-101 (R-1) : GENERAL NOTES AND SPECIFICATIONS
- AI-100-SB-01-129 (R-1) : DIMENSIONS

ONLY THE LATEST VERSION OF THIS DRG. AS INDICATED IN REVISION COLUMN IS VALID. THE PREVIOUS DRG. SHALL BE MARKED SUSPENDED AND REMOVED FROM SITE OF WORK.

NO.	DATE	BY	CHKD	REVISION
1	10/11/98	PV	REV	REV
2	10/11/98	PV	REV	REV

DIMENSIONS LISTED AS COLORED

SCALE 1:25, 20

CUSTOMER :

HOLTEC CONSULTING PRIVATE LIMITED

RAW MILL FEED HOPPER

G.A. & STRUCTURAL DETAIL OF HOPPER

DRG. NO. AI-06188-36-1-01

REV. 1