

Hejatex

PATENTED

MULTIFACE 1.5 FRAS

Two Component Material

for the Repair of Conveyor Belts in Underground Coal Mines

- ✓ **NO HAZARD TO PEOPLE, TRANSPORT AND STORAGE**
No toxic ingredients, no CMR constituents (carcinogenic, mutagenic and reprotoxic), no solvents, no dangerous goods in terms of transportation.
- ✓ **COMPLIANT WITH EN 14973 FOR USE IN UNDERGROUND MINES**
With electrical conductivity < 300 MΩ and self-extinguishing.
- ✓ **NO PRIMER.**
It does not require the preliminary use of solvents and primers
- ✓ **SIMPLE PREPARATION AND PROCEDURE**
Only 5 steps are required: roughening, cleaning the surface, applying Multiface® and rub it into the pores with a brush and filling up the damage.
- ✓ **LESS THAN 10 MINUTES HARDENING TIME**
The conveyor belt is ready for use after a very short time.
It also applies at temperature below freezing.
- ✓ **HIGH PERFORMANCE**
The chemical cross-link ensures the same resistance as conventional hot vulcanizing material, with the typical elasticity and dynamic strength.



MULTIFACE 1.5 FRAS

Two Component Material

for the Repair of Conveyor Belts in Underground Coal Mines

NON-TOXIC

MULTIFACE® is the only repair material on the market without any toxic ingredients.



FIRE RESISTANT & ANTISTATIC

Suitable for underground applications in coalmines (Surface resistance < 300 MΩ and self-extinguishing).



QUICK CURING

Very quick curing in less than 10 minutes permitting a return to service of the belt in very short time.



UNIVERSAL

Suitable for the repair of conveyor belt made of rubber, PWG, PVC and PU.



EASY TO APPLY

Extremely easy to apply with a comfortable processing time! Allows also making short interruptions during application.



ALMOST NO MATERIAL WASTE

Once opened, the cartridges can be resealed for using of the remaining quantity.



ULTRA RESISTANT

Resistant to salt water, oils, diesel, acids, alkalis and temperatures of -40°C/-40°F to +120°C/258°F.



Available versions: black self-levelling or black thixotropic/non-sag for vertical applications

STARTER SET with caulking gun

BLISTER PACK

Content	Starter set 50 g	Starter set 200 g	Starter set 400 g	Starter set 1500 g	Content	Blister pack 25 g	Blister pack 50 g
<ul style="list-style-type: none"> - 1 cartridge - 3 mixers - 1 caulking gun (Manual) - 1 spatula - 1 pair of gloves 					<ul style="list-style-type: none"> - 1 cartridge - 3 mixers - 1 piston - 1 spatula 		
Consumables	Cartridge 50 g	Cartridge 200 g	Cartridge 400 g	Cartridge 1500 g	Consumables	Cartridge 25 g	Cartridge 50 g

Vulcanizing Presses for Rubber belts - Heating Presses for Thermoplastic Belts - Tools for Belt Maintenance - Polymer Glues

Hejatex GmbH
Küstriner Straße 15
DE-94315 Straubing
Managing Director: Edgar Jakob

Phone: +49 - 94 21 - 96 88 4-0
Fax: +49 - 94 21 - 96 88 4-20
info@hejatex.com
www.hejatex.com

District Court Straubing
Commercial Register B 10835
VAT-Id.-Nr.: DE 813 335 594
Customs-Nr.: DE 5109647

Commerzbank Agency Straubing
Biz.: 742 400 62 - Konto: 66 27 111
BIC: COBADEFFXXX
IBAN: DE31 7424 0062 0662 7111 00

